

THE PERFECT RANGE FOR THE MOST DEMANDING MECHANICS Improve your productivity and boost your performance





- LESS OVERALL MAINTENANCE DUE TO LACK OF BRUSHES (LESS WEAR AND TEAR)
- OPERATES EFFECTIVELY AT ALL SPEEDS WITH RATED LOAD
- HIGHER SPEED RANGE AND LOWER ELECTRIC NOISE GENERATION
- HIGHER EFFICIENCY: MORE POWER LESS HEAT-LESS CONSUMPTION)
- MORF DURABLE





TWO YEARS GUARANTY In all Bahco Cordless tools





x1 BCL33IW2



x2

BCL33C1

BCL33IW2

BCL33IW2K1

18V 1/2" SQUARE DRIVE IMPACT WRENCH BRUSHLESS

PRODUCT DETAILS

- FOR HIGH TORQUE FASTENING OR UNFASTENING APPLICATIONS ON ANY TYPE OF VEHICLES INCLUDING AGRICULTURAL MACHINERY
- HIGH EFFICIENCY, MORE POWER, LOW MAINTENANCE, LONGER LIFESPAN BRUSHLESS ENGINE
- SQUARE DRIVE WITH RETAINING RING
- PROGRESSIVE TRIGGER
- · LED LIGHT TO BRIGHTEN THE WORKING AREA
- ONE-HAND FORWARD-REVERSE SWITCH
- BATTERY LEVEL INDICATOR IS ACTIVATED WITH THE TRIGGER
- THE KIT INCLUDES: THE TOOL + 2XBCL33B3 BATTERIES + BCL33C1 CHARGER
- DELIVERED INTO A BLOW MOULD CASE





V		min-1	Nm MAX	(min-1)
18V	1/2"	0 / 1700	1000	2000

2((m/sec-2		Kg
100.6	6.37	230/85/283	3,81









All measurements with battery BLCL33B3





All measurements with battery BLCL33B3







1.35 83.5 3.58 180/60/219







All measurements with battery BLCL33B3








18V 5Ah LI-ION BATTERY

BCL33B3



PRODUCT DETAILS

- · LITHIUM-ION BATTERIES HAVE BEST ENERGY WEIGHT RATIO VS NIMH OR OTHER TYPE OF LITHIUM BATTERIES
- THE POWER DELIVERED IS ALWAYS CONSTANT COMPARE TO OTHER BATTERY TYPES
- ON BOARD LEDS GAUGE SHOWING THE BATTERY CHARGE LEVEL
- OVERCHARGE PROTECTION AVOIDING HARMING THE BATTERY CELLS FOR LONGER LIFE
- SAFETY SHORT-CIRCUIT PROTECTION ON BATTERY PREVENTING CELLS DESTRUCTION
- CHARGING UP TO 100% TAKES AROUND 135' WITH THE STANDARD CHARGER AND 100' WITH THE QUICK CHARGER. THE CHARGING TIME DEPENDS ON THE REMAINING BATTERY CAPACITY LEVEL, THE CHARGING ENVIRONMENT AND THE AGE OF THE BATTERY
- BATTERY HOLDING SYSTEM PREVENTS FROM UNINTENDED DROP OFF
- AVAILABLE CHARGERS: STANDARD MODEL REF. BCL33C1 OR QUICK CHARGING MODEL REF. BCL33C2





BCL33C1 (NOT INCLUDED)



BCL33C2 (NOT INCLUDED)

BORN TO PERFORM




BCL33B1

18V 2Ah LI-ION BATTERY



PRODUCT DETAILS

- LITHIUM-ION BATTERIES HAVE BEST ENERGY WEIGHT RATIO VS NIMHOR OTHER TYPE OF LITHIUM BATTERIES
- THE POWER DELIVERED IS ALWAYS CONSTANT COMPARE TO OTHER BATTERY TYPES
- ON BOARD LEDS GAUGE SHOWING THE BATTERY CHARGE LEVEL
- OVERCHARGE PROTECTION AVOIDING HARMING THE BATTERY CELLS FOR LONGER LIFE
- SAFETY SHORT-CIRCUIT PROTECTION ON BATTERY PREVENTING CELLS DESTRUCTION
- CHARGING UP TO 100% TAKES AROUND 50' WITH THE STANDARD CHARGER AND 40' WITH THE QUICK CHARGER
- THE CHARGING TIME DEPENDS ON THE REMAINING BATTERY CAPACITY LEVEL, THE CHARGING ENVIRONMENT AND THE AGE OF THE BATTERY
- BATTERY HOLDING SYSTEM PREVENTS FROM UNINTENDED DROP OFF
- AVAILABLE CHARGERS: STANDARD MODEL REF. BCL33C1 OR QUICK CHARGING MODEL REF. BCL33C2





BCL33C1 (NOT INCLUDED)



BCL33C2 (NOT INCLUDED)

18V 2.3A BATTERY CHARGER

PRODUCT DETAILS

- THIS CHARGER OPERATES WITH ALL BAHCO 18V BATTERY PACKS
- THE BAHCO INTELLIGENT CHARGER PROTECTS THE BATTERY FROM OVERCURRENT, OVERCHARGE AND OVER TEMPERATURE PREVENTING DAMAGING THE BATTERY CELLS DURING CHARGING.
- CHARGING UP TO 100% A 2AH BATTERY PACK TAKES AROUND 50' AND FOR A 5.0 AH BATTERY PACK AROUND 135'. THE CHARGING TIME DEPENDS ON THE REMAINING BATTERY CAPACITY LEVEL, THE CHARGING ENVIRONMENT, AMBIENT TEMPERATURE AND THE AGE OF THE BATTERY
- THE CHARGER WILL AUTOMATICALLY STOP CHARGING WHEN THE BATTERY IS FULLY CHARGED
- LED 'S ON THE MAIN CHARGER BOARD INDICATES THE CURRENT CHARGING STATUS LEVEL OF THE BATTERY

iV	οV	A
240	18V Dc	2,3



18V 3.4A QUICK BATTERY CHARGER

PRODUCT DETAILS

- THIS CHARGER OPERATES WITH ALL BAHCO 18V BATTERY PACKS
- THE BAHCO INTELLIGENT CHARGER PROTECTS THE BATTERY FROM OVERCURRENT, OVERCHARGE AND OVER TEMPERATURE PREVENTING DAMAGING THE BATTERY CELLS DURING CHARGING.
- CHARGING UP TO 100% A 2AH BATTERY PACK TAKES AROUND 35' AND FOR A 5.0 AH BATTERY PACK AROUND 85'. THE CHARGING TIME DEPENDS ON THE REMAINING BATTERY CAPACITY LEVEL, THE CHARGING ENVIRONMENT, AMBIENT TEMPERATURE AND THE AGE OF THE BATTERY
- THE CHARGER WILL AUTOMATICALLY STOP CHARGING WHEN THE BATTERY IS FULLY CHARGED
- LEDS 'S ON THE MAIN CHARGER BOARD INDICATES THE CURRENT CHARGING STATUS LEVEL OF THE BATTERY









(NOT INCLUDED)

14.4V THE PERFECT BALANCE / COMPACTNESS & PERFORMANCE





BCL31C1

BCL33G1

BCL32G1K1

14.4V GREASER

PRODUCT DETAILS

- 14,4V GREASER FOR TRUCKS, TRAILERS, SEMI-TRAILERS. AGRICULTURAL AND CONSTRUCTION VEHICLES REQUESTING FREQUENT GREASING. SUITABLE ALSO FOR GENERAL MAINTENANCE AND INDUSTRIAL APPLICATIONS
- POWERFULL WITH 6,000PSI/414 BARS PRESSURE OUTPUT
- NO LOAD SPEED 70GR/MIN
- 400GR CARTRIDGE CAPACITY
- THE KIT INCLUDES: THE TOOL + 2XBCL32B1 BATTERIES + BCL31C1 CHARGER
- DELIVERED INTO A FABRIC BAG

V	PSI/ BARS	g/Min		
14,4V	6000/414	70	400g	750mm













150/60/226

1,32







All measurements with battery

8.14

97.8

















BCL32B1

14.4V 2Ah LI-ION BATTERY



PRODUCT DETAILS

- LITHIUM-ION BATTERIES HAVE BEST ENERGY WEIGHT RATIO VS NIMH OR OTHER TYPE OF LITHIUM BATTERIES
- THE POWER DELIVERED IS ALWAYS CONSTANT COMPARE TO OTHER BATTERY TYPES
- ON BOARD LEDS GAUGE SHOWING THE BATTERY CHARGE LEVEL
- OVERCHARGE PROTECTION AVOIDING HARMING THE BATTERY CELLS FOR LONGER LIFE
- SAFETY SHORT-CIRCUIT PROTECTION ON BATTERY PREVENTING CELLS DESTRUCTION
- CHARGING UP TO 100% TAKES AROUND 40'. THE CHARGING TIME DEPENDS ON THE REMAINING BATTERY CAPACITY LEVEL, THE CHARGING ENVIRONMENT AND THE AGE OF THE BATTERY
- BAHCO CHARGER FOR THIS BATTERY PACK: REF. BCL31C1

V	Ah	⊙ ←Ⅲ BCL33C1
18V	2Ah	100% 40'
	Kg	
87/59/105	0,32	





















4.00

200/54/191

1,03

83.9





BCL31IS1

BCL31SD1

BCL31D1

BATTERY

PRODUCT DETAILS

• LITHIUM-ION BATTERIES HAVE BEST ENERGY WEIGHT RATIO VS NIMH OR OTHER TYPE OF LITHIUM BATTERIES

BCL31IW1

- THE POWER DELIVERED IS ALWAYS CONSTANT COMPARE TO OTHER BATTERY TYPES
- ON BOARD LEDS GAUGE SHOWING THE BATTERY CHARGE LEVEL
- OVERCHARGE PROTECTION AVOIDING HARMING THE BATTERY CELLS FOR LONGER LIFE
- SAFETY SHORT-CIRCUIT PROTECTION ON BATTERY PREVENTING CELLS DESTRUCTION
- CHARGING UP TO 100% TAKES AROUND 40'. THE CHARGING TIME DEPENDS ON THE REMAINING BATTERY
 CAPACITY LEVEL, THE CHARGING ENVIRONMENT AND THE AGE OF THE BATTERY
- BAHCO CHARGER FOR THIS 12V BATTERY PACK: REF.BCL31C1



0,19

61/54/85







BCL31C1

12/14.4V BATTERY CHARGER



PRODUCT DETAILS

- THIS CHARGER IS A DUAL VOLTAGE UNIT OPERATING ALL BAHCO 12V & 14.4V BATTERY PACKS
- THE BAHCO INTELLIGENT CHARGER PROTECTS THE BATTERY FROM OVERCURRENT, OVERCHARGE AND OVER TEMPERATURE PREVENTING DAMAGING THE BATTERY CELLS DURING CHARGING.
- CHARGING UP TO 100% TAKES AROUND 40'. THE CHARGING TIME DEPENDS ON THE REMAINING BATTERY CAPACITY LEVEL, THE CHARGING ENVIRONMENT, AMBIENT TEMPERATURE AND THE AGE OF THE BATTERY
- THE CHARGERS WILL AUTOMATICALLY STOP CHARGING WHEN THE BATTERY IS FULLY CHARGED
- · LEDS 'S ON THE MAIN CHARGER BOARD INDICATES THE CURRENT CHARGING STATUS LEVEL OF THE BATTERY

iV	οV	A
240 V AC	12/14,4 DC	3





THE PERFECT MATCH: ALL POWER TOOLS ACCESSORIES TO COVER YOUR NEEDS



Discover all we can offer at www.bahco.com







WWW.BAHCO.COM